








## Quarz-Programm von Hong Kong X'tals bei Bindel Elektronik AG ab Lager lieferbar

<b>HC 49 U</b>		HKC Typ:	9U
		Toleranz:	30ppm
		Temp. Bereich	-10 - + 60°C
		Löten:	THT
Frequenz MHz	pF	Bindel Nr.	
4.000000	12 pF	806137	
4.194304	12 pF	806070	
4.433619	Serial	806071	
6.000000	16 pF	806072	
7.372800	16 pF	806138	
8.000000	30 pF	806073	
10.240000	18 pF	806074	
13.522500	20 pF	806075	
13.560000	30 pF	806076	
16.000000	30 pF	806077	
20.000000	18 pF	806139	
24.576000	12 pF	806078	
54.000000	10 pF	806079	

<b>HC 49 US</b>		HKC Typ:	9S
		Toleranz:	30ppm
		Temp. Bereich	-10 - + 60°C
		Löten:	THT
Frequenz	pF	Bindel Nr.	
3.250000	20 pF	806080	
4.000000	18 pF	806140	
4.194304	12 pF	806081	
4.332000	20 pF	806082	
4.915200	Serial	806147	
5.000000	20 pF	806144	
6.000000	Serial	806085	
7.200000	10 pF	806086	
7.680000	30 pF	806087	
8.000000	20 pF	806088	
9.830400	30 pF	806089	
10.000000	12 pF	806090	
11.059200	Serial	806091	
12.000000	32 pF	806092	
13.560000	20 pF	806093	
14.318180	20 pF	806094	
14.745600	20 pF	806095	
16.000000	30 pF	806165	
16.934400	30 pF	806098	
17.734475	10 pF	806097	
18.000000	22 pF	806099	
18.432000	Serial	806100	
19.660800	18 pF	806101	
20.000000	20pF	806102	
20.480000	18pF	806104	
22.118400	16pF	806105	
24.000000	32pF	806160	
24.576000	18 pF	806106	
25.000000	18 pF	806108	
27.000000	16 pF	806109	

<b>HC 49 SMD</b>		HKC Typ:	SS
		Toleranz:	30ppm
		Temp. Bereich	-10 - + 60°C
		Löten:	SMD
Frequenz	pF	Bindel Nr.	
3.250000	20 pF	806111	
4.000000	18 pF	806141	
4.194304	12 pF	806112	
4.332000	20 pF	806113	
4.500000	20 pF	806114	
4.915200	Serial	806143	
5.000000	20 pF	806115	
6.000000	Serial	806145	
7.200000	10 pF	806116	
7.372800	20 pF	801190	
7.680000	30 pF	806149	
8.000000	20 pF	806150	
9.830400	30 pF	806117	
10.000000	12 pF	806118	
11.059200	Serial	806151	
12.000000	32 pF	806154	
13.560000	20 pF	806119	
14.318180	20 pF	801120	
14.745600	20 pF	801291	
16.000000	30 pF	801304	
16.934400	30 pF	806122	
17.734475	10 pF	806123	
18.000000	22 pF	806124	
18.432000	Serial	806125	
19.660800	18 pF	806155	
20.000000	20 pF	806156	
24.480000	18 pF	806126	
22.184000	16 pF	806127	
24.000000	32 pF	806157	
24.576000	18 pF	806128	
25.000000	20 pF	806158	
27.000000	16 pF	806129	
30.000000	20 pF	806159	

<b>5032</b>		HKC Typ:	CA
		Toleranz:	30ppm
		Temp. Bereich	-10 - + 60°C
		Löten:	SMD
Frequenz	pF	Bindel Nr.	
8.000000	10 pF	806130	
9.830400	10 pF	806131	
12.000000	8 pF	806132	
13.521270	10 pF	806133	
14.745600	16 pF	806134	
15.360000	18 pF	806135	
24.000000	20 pF	806136	

<b>Uhrenquarze 32.768 KHz</b>		
Toleranz:	20ppm	
Temp. Bereich	-20 - + 70°C	
Lastkapazität	12.5 pF	
Abbildung	Typ	Bindel Nr.
	2T	806162
	3T	806163
	M3	806164